

JB4QA

"JBQA": SCATOLA DI GIUNZIONE ATEX EQUALIZZATA, FINO A 4 CELLE DI CARICO



Scatola di giunzione IP67 a 4 ingressi, dotata di scheda elettronica per unione ed equalizzazione di 2, 3 o 4 celle di carico. Morsettiere a vite per agevolare il collegamento e trimmer di regolazione del segnale, per una equalizzazione precisa ed affidabile. Marcatura: ATEX II 2G Ex ib IIC T6 Gb per gas. ATEX II 2D Ex tb IIIC T115°C Db IP65 per polveri.

La soluzione ideale per
applicazioni industriali
avanzate

CARATTERISTICHE TECNICHE

- Involucro in ABS. Grado di protezione: IP67.
- Massima tensione in ingresso: 24Vdc.
- Massima corrente in ingresso: 700mA.
- Massimo segnale cella in ingresso: 1000mV.
- Effetto della temperatura: 50ppm/°C.
- Dimensioni (lxwxh): 120x80x55mm



DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE